



# Product Specifications

## LF670



### Lube, Full-Flow Spin-On

Fleetguard® LF670 spin-on lube filter meets or exceeds OE performance requirements and the new challenges of modern engine technology.

[View product on Fleetguard.com](http://Fleetguard.com)

## Specifications

Thread Size	1 1/2-12 UNS-2B	Gasket OD	4.35 inch
Gasket Inside Diameter	3.84 inch	Length	9.81 inch
Largest OD	4.74 inch	Media Type	Cellulose
Hydrostatic Burst Minimum	246.4999999999997 psi	Rated Flow	151.4 L/m

## Related Parts

<b>Uses Service Part</b>	3318568S 3305000S	3303782S 3001483S	3302630S 3927995S	3302631S
<b>For Upgrade, Use</b>	LF9325	LF3363		
<b>Replaces</b>	LF670SC			

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2024 Cummins Filtration Inc. All Rights Reserved